HARDI MINIDRIFT DUO

Air inclusion nozzles



MINIDRIFT DUC

HARDI MINIDRIFT DUO Air inclusion nozzles

The HARDI MINIDRIFT DUO nozzle can be used for spraying under sub-optimal weather conditions when spraying cannot be postponed. The MINIDRIFT DUO nozzle will at low pressures reduce drift to a minimum.

- Working pressure: 1.5 to 6 bar
- ISO flow, colours, sizes and nomenclature
- 30° forward and backward angle
- Application rates from 125 to 420 l/ha (at 8 km/h)
- SYNTAL precision moulded thermoplastic

This compact flat spray air-injector nozzle offers droplet spectrum from medium to very coarse; safe for drift control but without risking poor coverage and deposition on leaves. The two angled fans increase the number of droplets and impacts on target compared to normal air injector nozzles. This improves the coverage on dense foliage and vertical targets.

The injector can easily be removed for cleaning the nozzle.

The HARDI MINIDRIFT DUO nozzles can be mounted using the 334083 ISO cap.

	, in the second				l/ha at km/h							
	bar	l/min	<i>.</i> ///%	6	7	8	10	12	14	16	18	
	SYNTAL-S 37218100											
	1.5	0.84	VC	168	144	126	101	84	72	63	56	
9	2.0	0.97	VC	194	166	146	116	97	83	73	65	
03.Blue	2.5	1.08	С	216	185	162	130	108	93	81	72	
	3.0	1.19	С	238	204	179	143	119	102	89	79	
	4.0	1.37	М	274	235	206	164	137	117	103	91	
	5.0	1.53	М	310	266	232	186	155	124	93	74	
	6.0	1.68	М	336	288	252	202	168	144	126	112	

	SYNTAL-S 37218200											
	1.5	1.12	VC	224	192	168	134	112	96	84	75	
σ	2.0	1.29	С	258	221	194	155	129	111	97	86	
å	2.5	1.44	С	288	247	216	173	144	123	108	96	
4-	3.0	1.58	С	316	271	237	190	158	135	119	105	
0	4.0	1.82	M	364	312	273	218	182	156	137	121	
	5.0	2.04	M	408	350	306	245	204	175	153	136	
	6.0	2.23	М	446	382	335	268	223	191	167	149	

	SYNTA	L-S 3721	8300								
_	1.5	1.39	VC	278	238	209	167	139	119	104	93
3	2.0	1.61	С	322	276	242	193	161	138	121	107
5	2.5	1.80	С	360	309	270	216	180	154	135	120
ė	3.0	1.97	С	394	338	296	236	197	169	148	131
D U	4.0	2.28	М	456	391	342	274	228	195	171	152
ľ	5.0	2.55	М	510	437	383	306	255	219	191	170
	6.0	2.79	М	558	478	419	335	279	239	209	186



 Spray quality: Very Fine (VF), Fine (F), Medium (M), Coarse (C), Very Coarse (VC).







Høje Taastrup, Denmark







USA



Nørre Alslev. Denmark



Spain



Australia

HARDI INTERNATIONAL A/S is an international group whose basic idea is to satisfy the user's requirements for quality products which ensure efficient, punctual and precise application of crop protection products. Our world-wide distribution and sales network comprise more than 100 countries where we are represented by importers, agents and sales subsidiaries. These are situated in Sweden, Norway, Denmark, the UK, France, Spain, North America, Germany and Australia.

Since 1957 HARDI has committed to the ever-increasing demands for efficient and precise plant protection. HARDI is the trendsetter within application of crop protection products. To achieve this position continued developments and innovation are essential. HARDI is committed to the long term future of plant protection.

Read more at www.hardi-international.com

HARDI INTERNATIONAL A/s

Helgeshøj Allé 38 • DK 2630 • Taastrup • Denmark E-Mail: hardi@hardi-international.com • www. hardi-international.com

HARDI - Your Sprayer Specialist